



# IQ8 Series Microinverters

Our newest IQ8 Microinverters are the industry’s first microgrid-forming\*, software-defined microinverters with split-phase power conversion capability to convert DC power to AC power efficiently. The brain of the semiconductor-based microinverter is our proprietary application-specific integrated circuit (ASIC), which enables the microinverter to operate in grid-tied or off-grid modes. This chip is built in advanced 55-nm technology with high-speed digital logic and has superfast response times to changing loads and grid events, alleviating constraints on battery sizing for home energy systems.



Part of the Enphase Energy System, IQ8 Series Microinverters integrate with the Enphase IQ Battery, Enphase IQ Gateway, and the Enphase App monitoring and analysis software.



IQ8 Series Microinverters redefine reliability standards with more than one million cumulative hours of power-on testing, enabling an industry-leading limited warranty of up to 25 years.



Connect PV modules quickly and easily to IQ8 Series Microinverters using the included Q-DCC-2 adapter cable with plug-and-play MC4 connectors.



IQ8 Series Microinverters are UL Listed as PV rapid shutdown equipment and conform with various regulations, when installed according to manufacturer’s instructions.

\* Meets UL 1741 only when installed with IQ System Controller 2 or 3. IQ8H-208 V operates only in grid-tied mode.  
 \*\* IQ8 Series Microinverters support split-phase, 240 V. IQ8H-208 support single-phase, 208 V only.

## Easy to install

- Lightweight and compact with plug-and-play connectors
- Power line communication (PLC) between components
- Faster installation with simple two-wire cabling

## High productivity and reliability

- Produce power even when the grid is down\*
- More than one million cumulative hours of testing
- Class II double-insulated enclosure
- Optimized for the latest high-powered PV modules

## Microgrid-forming

- Complies with the latest advanced grid support\*\*
- Remote automatic updates for the latest grid requirements
- Configurable to support a wide range of grid profiles
- Meets CA Rule 21 (UL 1741-SA) and IEEE 1547:2018 (UL 1741-SB)

## Note:

- IQ8 Microinverters cannot be mixed with previous generations of Enphase microinverters (IQ7 Series, IQ6 Series, and so on) in the same system.
- IQ Microinverters ship with default settings that meet North America’s IEEE 1547 interconnection standard requirements. Region-specific adjustments may be requested by an Authority Having Jurisdiction (AHJ) or utility representative, according to the IEEE 1547 interconnection standard. An IQ Gateway is required to make these changes during installation.

# IQ8 Series Microinverters

INPUT DATA (DC)	UNITS	IQ8-60-2-US	IQ8PLUS-72-2-US	IQ8M-72-2-US	IQ8A-72-2-US	IQ8H-240-72-2-US	IQ8H-208-72-2-US <sup>1</sup>	
Commonly used module pairings <sup>2</sup>	W	235-350	235-440	260-460	295-500	320-540	295-500	
Module compatibility	—	To meet compatibility, PV modules must be within the maximum input DC voltage and maximum module I <sub>sc</sub> . Module compatibility can be checked at <a href="https://enphase.com/installers/microinverters/calculator">https://enphase.com/installers/microinverters/calculator</a>						
MPPT voltage range	V	27-37	27-45	30-45	32-45	36-45	36-45	
Operating range	V	16-48			16-58			
Min./Max. start voltage	V	22/48			22/58			
Max. input DC voltage	V	50			60			
Max. continuous input DC current	A	10			12			
Max. input DC short-circuit current	A				25			
Max. module I <sub>sc</sub>	A				20			
Overvoltage class DC port	—				II			
DC port backfeed current	mA				0			
PV array configuration	—	Ungrounded array; No additional DC side protection required; AC side protection requires max 20A per branch circuit						
OUTPUT DATA (AC)	UNITS	IQ8-60-2-US	IQ8PLUS-72-2-US	IQ8M-72-2-US	IQ8A-72-2-US	IQ8H-240-72-2-US	IQ8H-208-72-2-US <sup>1</sup>	
Peak output power	VA	245	300	330	366	384	366	
Max. continuous output power	VA	240	290	325	349	380	360	
Nominal (L-L) grid voltage	V	240, split-phase (L-L), 180°						208, single-phase (L-L), 120°
Max. continuous output current	A	1.0	1.21	1.35	1.45	1.58	1.73	
Min./Max. grid voltage <sup>3</sup>	—	211-264						183-250
Nominal frequency	Hz	60						
Extended frequency range	Hz	47-68						
AC short-circuit fault current over 3 cycles	Arms	2						4.4
Max. units per 20 A (L-L) branch circuit <sup>4</sup>	—	16	13	11	11	10	9	
Total harmonic distortion	—	<5%						
Overvoltage class AC port	—	III						
AC port backfeed current	mA	30						
Power factor setting	—	1.0						
Grid-tied power factor (adjustable)	—	0.85 leading ... 0.85 lagging						
Peak efficiency	%	97.7	97.7	97.8	97.7	97.6	97.5	
CEC weighted efficiency	%	97	97	97.5	97	97	97	
Nighttime power consumption	mW	23	25	21	22	22	15	

(1) IQ8H-208 operates in grid-tied mode only at 208 VAC.

(2) No enforced DC/AC ratio.

(3) Nominal voltage range can be extended beyond nominal if required by the utility.

(4) Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

MECHANICAL DATA	
Ambient temperature range	-40°C to 60°C (-40°F to 140°F)
Relative humidity range	4% to 100% (condensing)
DC connector type	MC4
Dimensions (H x W x D)	212 mm (8.3") x 175 mm (6.9") x 30.2 mm (1.2")
Weight	1.08 kg (2.38 lb)
Cooling	Natural convection – no fans
Approved for wet locations	Yes
Pollution degree	PD3
Enclosure	Class II double-insulated, corrosion-resistant polymeric enclosure
Environmental category/UV exposure rating	NEMA Type 6/outdoor

COMPLIANCE	
Certifications	<p>CA Rule 21 (UL 1741-SA), UL 62109-1, IEEE 1547:2018 (UL 1741-SB), FCC Part 15 Class B, ICES-0003 Class B, CAN/CSA-C22.2 NO. 107.1-01.</p> <p>This product is UL Listed as PV rapid shutdown equipment and conforms with NEC 2014, NEC 2017, NEC 2020, and NEC 2023 section 690.12 and C22.1-2018 Rule 64-218 rapid shutdown of PV Systems, for AC and DC conductors, when installed according to manufacturer's instructions.</p>

# Revision history

REVISION	DATE	DESCRIPTION
DSH-00378-1.0	February 2024	<ul style="list-style-type: none"><li>• Updated the information about IEEE 1547 interconnection standard requirements</li><li>• Updated nighttime power consumption value.</li><li>• Updated peak efficiency percentage.</li><li>• Updated input DC data specifications.</li></ul>